vsf fahrradmanufaktur®
Premium Mobilität

TX-400

Shimano Deore XT 30-speed / HS33

Article	Inch	Frame size	Color
102220031	26"	Gents, 47 cm	blackolive matt
102220032	26"	Gents, 52 cm	blackolive matt
102220033	26"	Gents, 57 cm	blackolive matt
102220035	26"	Ladies, 45 cm	blackolive matt
102220036	26"	Ladies, 50 cm	blackolive matt

Technical changes and changes in equipment reserved, color deviations possible.

General	**Frame**	25 CrMo 4, double butted
	Head set	Ritchey Comp Logic V2
	Fork	26" 25CrMo 4
	Shifting System	Shimano Deore XT RD-T8000, 10-speed
	Derailleur	Shimano Deore XT FD-T8000, 3-speed
	Brakes	Magura HS33, incl. Brakebooster
	Headlight	Busch & Müller Lumotec IQ-XS, 70 LUX
	Rear light	Busch & Müller, Toplight Mini Plus
	Carrier	Tubus Cargo / Tubus Tara Lowirder
	Saddle	Selle Royal Scientia
	Seat post	Humpert Ergotec Skalar, patent, aluminum, 27,2 mm, 400 mm, safety level 6
	Pedals	VP-196 aluminum
	Kickstand	0611, rear kickstand
	Chainguard	Shimano chainguard
	Mudguard	SKS, plastic
	Other	maximum weight allowed 140 kg
	Weight	15,9 kg
Cockpit	**Stem**	Humpert Ergotec Piranha 2, 31,8 mm, safety level 6
	Handlebars	Humpert Ergotec Trekking, aluminum, 620 mm, safety level 6
	Grips	Ergon GP3, with clamp and integrated bar ends
	Shift lever	Shimano Deore SL-M6000, 3-/10-speed
	Brake lever	Magura HS33
Wheels/Tires/Drivetrain	**Tires**	Schwalbe Marathon Mondial, 50-559, reflex
	Rims	Schürmann YAK19 aluminum, 36 holes
	Spokes	Niro ED 2,34 mm
	Front Hub	Shutter Precission PV-8, hub dynamo, 36 holes
	Rear Hub	Shimano Deore FH-T610, 36 holes
	Sprocket	Shimano CS-HG500, 10-speed, 11-34 teeth
	Chain	KMC X10
	Inner bearing	Shimano BB-S300, Octalink, BSA
	Bottom bracket	Shimano Deore FC-T521, 170 mm, Octalink, 48/36/26 teeth
	Gear ratio (f:r)	48/36/26 teeth : 11-36 teeth