



T-700

Shimano Deore XT 30-speed / HS22

Article	Inch	Frame size	Color
102220091	28"	Gents, 52 cm	ebony matt
102220092	28"	Gents, 57 cm	ebony matt
102220093	28"	Gents, 62 cm	ebony matt
102220095	28"	Ladies, 45 cm	ebony matt
102220096	28"	Ladies, 50 cm	ebony matt
102220097	28"	Anglais, 55 cm	ebony matt
102220101	28"	Gents, 52 cm	slate matt
102220102	28"	Gents, 57 cm	slate matt
102220103	28"	Gents, 62 cm	slate matt
102220105	28"	Ladies, 45 cm	slate matt
102220106	28"	Ladies, 50 cm	slate matt
102220107	28"	Anglais, 55 cm	slate matt

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	25 CrMo 4, double butted
	Head set	Ritchey Comp Logic V2
	Fork	28" aluminum
	Shifting System	Shimano Deore XT RD-T8000, 10-speed
	Derailleur	Shimano Deore XT FD-T8000, 3-speed
	Brakes	Magura HS22, incl. Brakebooster
	Headlight	Busch & Müller Lumotec IQ-XS, 70 LUX
	Rear light	Busch & Müller, Toplight 2C
	Carrier	Racktime Light-it
	Saddle	Selle Royal Essenza
	Seat post	Levelnine, patent, aluminum, 27,2 mm, 300 mm
	Pedals	Marwi SP-823
	Kickstand	Comp Zoom, rear kickstand
	Chainguard	Shimano chainguard
Cockpit	Mudguard	SKS, plastic
	Other	maximum weight allowed 140 kg
	Weight	13,9 kg
	Stem	Levelnine, aluminum, a-head, 25,4 mm
	Handlebars	Levelnine, Trekking, aluminum, 640 mm
Wheels/Tires/Drivetrain	Grips	Ergon GP1, with clamp
	Shift lever	Shimano Deore XT SL-T8000, 3-/10-speed, with gear display
	Brake lever	Magura HS22, 3-fingerlever
	Tires	Schwalbe Marathon Supreme, 42-622, reflex
	Rims	Schürmann YAK19 aluminum, 36 holes
	Spokes	Niro 2,0 mm
	Front Hub	Shutter Precision PV-8, hub dynamo, 36 holes
	Rear Hub	Shimano Deore FH-T610, 36 holes
	Sprocket	Shimano Deore XT CS-M771, 10-speed, 11-36 teeth
	Chain	KMC X10
	Inner bearing	Shimano Deore SM-BB52, for Hollowtech II, BSA
	Bottom bracket	Shimano Deore XT FC-T8000, 170 mm, Hollowtech II, 48/36/26 teeth
	Gear ratio (f:r)	48/36/26 teeth : 11-36 teeth