



TX-1000

Rohloff Speedhub 14-speed / Disc / Gates

Article	Inch	Frame size	Color
102320045	27.5"	Gents, 52 cm	ebony matt
102320046	27.5"	Gents, 57 cm	ebony matt
102320047	27.5"	Gents, 62 cm	ebony matt

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	25 CrMo 4, double butted
	Head set	Ritchey Comp Logic V2
	Fork	27,5" 25CrMo 4
	Shifting System	Rohloff Speedhub, 14-speed
	Derailleur	---
	Brakes	Shimano Deore XT BR-M8100 (front 203 mm / rear 203 mm)
	Headlight	Supernova E3 Pro 2, 70 LUX
	Rear light	Supernova, E3 Tail Light 2
	Carrier	Tubus Logo Evo / Tubus Tara Lowrider
	Saddle	Ergon ST Core Prime
	Seat post	Humpert Ergotec Skalar, patent, aluminum, 27.2 x 400 mm, safety level 6
	Pedals	VP-196 Aluminum
	Kickstand	Rex HV, rear kickstand
	Chainguard	Gates chain guard
	Mudguard	SKS, plastic
Cockpit	Other	max load 170 kg
	Weight	17.4 kg
	Stem	Humpert Ergotec Piranha 2, 31,8 mm, safety level 6
	Handlebars	Humpert Ergotec Trekking, Aluminum, 620 mm, safety level 6
	Grips	Ergon GP3, with clamp and integrated Barends
	Shift lever	Rohloff twist shifter
Wheels/Tires/Drivetrain	Brake lever	Shimano Deore XT BL-T8100, 3-finger-brake lever
	Tires	Schwalbe Marathon Mondial, 50-584, reflex
	Rims	Ryde Andra 40 Disc Aluminum hollow section, 32 holes
	Spokes	Niro ED 2,34 mm
	Front Hub	SON 28, 12 x 100 mm, hub dynamo, Centerlock, 32 holes
	Rear Hub	Rohloff Speedhub 14 speed, Disc, 32 holes
	Sprocket	Gates CDX, 20 teeth
	Chain	Gates CDX-drive belt
	Inner bearing	FSA
	Bottom bracket	Gates S550, Aluminum, 170 mm, Gates CDX 55 teeth with chain guard
	Gear ratio (f:r)	55 teeth : 20 teeth