



T-700

Shimano Deore XT 30-speed / HS22

Article	Inch	Frame size	Color
102320091	28"	Gents, 52 cm	ebony matt
102320092	28"	Gents, 57 cm	ebony matt
102320093	28"	Gents, 62 cm	ebony matt
102320095	28"	Ladies, 45 cm	ebony matt
102320096	28"	Ladies, 50 cm	ebony matt
102320097	28"	Anglais, 55 cm	ebony matt
102320101	28"	Gents, 52 cm	slate matt
102320102	28"	Gents, 57 cm	slate matt
102320103	28"	Gents, 62 cm	slate matt
102320105	28"	Ladies, 45 cm	slate matt
102320106	28"	Ladies, 50 cm	slate matt
102320107	28"	Anglais, 55 cm	slate matt

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	25 CrMo 4, double butted
	Head set	Ritchey Comp Logic V2
	Fork	28" Aluminium
	Shifting System	Shimano Deore XT RD-T8000, 10-speed
	Derailleur	Shimano Deore XT FD-T8000, 3-speed
	Brakes	Magura HS22, included Brakebooster
	Headlight	Busch & Müller Lumotec IQ-XS, 70 LUX
	Rear light	Busch & Müller, Toplight 2C
	Carrier	Racktime Light-it, strutless, without spring flap
	Saddle	Selle Royal Essenza
	Seat post	Levelnine, patent, aluminum, 27,2 mm, 300 mm
	Pedals	Marwi SP-823, black
	Kickstand	Zoom, rear kickstand
Cockpit	Chainguard	Shimano chain guard
	Mudguard	SKS, plastic
	Other	max load 140 kg
	Weight	13.9 kg
Wheels/Tires/Drivetrain	Stem	Levelnine, Aluminium, a-head, 25,4 mm
	Handlebars	Levelnine, Trekking, Aluminium, 640 mm
	Grips	Ergon GP1, with clamp
	Shift lever	Shimano Deore XT SL-T8000, 3-/10-speed, with Display
	Brake lever	Magura HS22, 3-fingerbrake lever
	Tires	Schwalbe Marathon Efficiency, 40-622, reflex
	Rims	Schürmann YAK19 Aluminium hollow section, 36 holes
	Spokes	Niro 2,0 mm
	Front Hub	Shutter Precision PV-8, hub dynamo, 36 holes
	Rear Hub	Shimano Deore FH-T610, 36 holes
	Sprocket	Shimano Deore XT CS-M771, 10-speed, 11-36 teeth
	Chain	KMC X10
	Inner bearing	Shimano Deore SM-BB52, für Hollowtech II, BSA
	Bottom bracket	Shimano Deore XT FC-T8000, 170 mm, Hollowtech II, 48/36/26 teeth
	Gear ratio (f:r)	48/36/26 teeth : 11-36 teeth