



GX-700

SRAM Apex XPLR AXS 12-speed / Disc

Article	Inch	Frame size	Color
102320848	28"	Gents, 48 cm	wet terra matt
102320851	28"	Gents, 51 cm	wet terra matt
102320854	28"	Gents, 54 cm	wet terra matt
102320857	28"	Gents, 57 cm	wet terra matt
102320860	28"	Gents, 60 cm	wet terra matt

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	25 CrMo 4, double butted
	Head set	Acros AZX-228, 1 1/8"-1,5", External Cup
	Fork	vsf fm Gravel 28" aluminum, 12 x 100 mm, Flatmount, tapered
	Shifting System	SRAM Apex XPLR AXS, 12-speed
	Derailleur	---
	Brakes	SRAM Apex (front 160 mm / rear 160 mm), Flatmount
	Headlight	---
	Rear light	---
	Carrier	---
	Saddle	Selle Italia Model Y
	Seat post	Ritchey WCS Carbon Link Flexilogic, 27.2 mm, 350 mm
	Pedals	---
	Kickstand	---
	Chainguard	---
	Mudguard	---
Cockpit	Other	max load 120 kg, vsf fahrradmanufaktur Enamel-Mug
	Weight	11.3 kg
	Stem	Levelnine, aluminum, 6°, (90 / 90 / 90 / 110 / 110 mm)
	Handlebars	Levelnine Gravel, aluminum, Flare 12°, (440 / 440 / 440 / 460 / 480 mm)
	Grips	Fizik Vento Solocush Tacky handlebar tape, 2,7 mm thick, black
	Shift lever	SRAM Apex XPLR AXS , 12-speed
Wheels/Tires/Drivetrain	Brake lever	SRAM Apex XPLR AXS , 12-speed
	Tires	Schwalbe G-One R, 45-622
	Rims	Ryde Dutch 19, Disc, 32 holes
	Spokes	Niro 2,0 mm black
	Front Hub	Shutter Precision PL-7, 12 x 100 mm, hub dynamo, Centerlock, 32 holes
	Rear Hub	KT, 12 x 142 mm , Centerlock, 32 holes
	Sprocket	SRAM XPLR PG-1231, 12-speed, 11-44 teeth
	Chain	SRAM Apex , 12-speed
	Inner bearing	SRAM DUB, BSA
	Bottom bracket	SRAM Apex, 40 teeth, 170 mm
	Gear ratio (f:r)	40 teeth : 11-44 teeth