



T-700 LTD

Shimano Deore XT 30-speed / HS22

Article	Inch	Frame size	Color
102520601	28"	Gents, 52 cm	slate glossy
102520602	28"	Gents, 57 cm	slate glossy
102520603	28"	Gents, 62 cm	slate glossy
102520605	28"	Ladies, 45 cm	midnight glossy
102520606	28"	Ladies, 50 cm	midnight glossy
102520607	28"	Ladies, 55 cm	midnight glossy

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	25 CrMo 4, double butted
	Head set	Ritchey Comp Logic V2
	Fork	28" aluminum
	Shifting System	Shimano Deore XT RD-T8000, 10-speed
	Derailleur	Shimano Deore XT FD-T8000, 3-speed
	Brakes	Magura HS22, incl. Brakebooster
	Headlight	Busch & Müller Lumotec IQ-XS, 70 LUX
	Rear light	Busch & Müller, Toplight 2C plus
	Carrier	Racktime Light-it
	Saddle	Selle Royal Essenza
	Seat post	Humpert Ergotec Atar, aluminum, 27,2 mm, 300 mm
	Pedals	Marwi SP-823
	Kickstand	Atran Velo Parko, rear kickstand
	Chainguard	Shimano chainguard
Mudguard	SKS, plastic	
Other	maximum weight allowed 140 kg	
Weight	13,9 kg	
Cockpit	Stem	Levelnine, aluminum, a-head, 25,4 mm
	Handlebars	Levelnine, Trekking, aluminum, 640 mm
	Grips	Ergon GP1, with clamp
	Shift lever	Shimano Deore XT SL-T8000, 3-/10-speed, with gear display
Brake lever	Magura HS22, 3-fingerlever	
Wheels/Tires/Drivetrain	Tires	Schwalbe Marathon Racer, 40-622, reflex
	Rims	Schürmann YAK19 aluminum, 36 holes
	Spokes	Niro 2,0 mm
	Front Hub	Shutter Precision PV-8, hub dynamo, 36 holes
	Rear Hub	Shimano Deore FH-T610, 36 holes
	Sprocket	Shimano Deore XT CS-M771, 10-speed, 11-36 teeth
	Chain	KMC X10
	Inner bearing	Shimano BB-MT501, für Hollowtech II, BSA
Bottom bracket	Shimano Deore XT FC-T8000, 170 mm, Hollowtech II, 48/36/26 teeth	
Gear ratio (f:r)	48/36/26 teeth : 11-36 teeth	