



GX-600

Shimano GRX RX822 12-speed / disc

Article	Inch	Frame size	Color
102620111	28"	Gents, 48 cm	emerald matt
102620112	28"	Gents, 51 cm	emerald matt
102620113	28"	Gents, 54 cm	emerald matt
102620114	28"	Gents, 57 cm	emerald matt
102620115	28"	Gents, 60 cm	emerald matt

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	25 CrMo 4, double butted, suspension-fork-ready
	Head set	Acros AZX-228, 1 1/8"-1,5", external cup
	Fork	vsf fm Gravel carbon, 12 x 100 mm, flatmount, tapered
	Shifting System	Shimano GRX RD-RX822-SGS, 12-speed
	Derailleur	---
	Brakes	Shimano GRX BR-RX410 (front 160 mm / rear 160 mm), flatmount
	Headlight	---
	Rear light	---
	Carrier	---
	Saddle	SQlab 611
	Seat post	Ritchey WCS Carbon Link Flexilogic, 27.2 mm, 350 mm
	Pedals	Marwi SP-102, flat pedal, aluminium, black
	Kickstand	---
	Chainguard	---
	Mudguard	---
Cockpit	Other	max load 130 kg
	Weight	11,2 kg
	Stem	Levelnine, aluminium, 6°, (75 / 75 / 90 / 90 / 110 mm)
	Handlebars	Levelnine Gravel, aluminium, Flare 12°, (420 / 420 / 440 / 440 / 440 mm)
	Grips	Fizik Vento Solocush Tacky, black
	Shift lever	Shimano GRX ST-RX610, 1-/12-speed
Wheels/Tires/Drivetrain	Brake lever	Shimano GRX ST/BL-RX610, 1-/12-speed
	Tires	Schwalbe G-One R Raceguard, 50 x 622, TLE
	Rims	Newmen Performance 30 Light, 28 holes, tubeless-ready
	Spokes	Niro, black
	Front Hub	Shimano HB-TC500, Centerlock, 28 holes
	Rear Hub	Shimano SLX FH-TM7110, Centerlock, 28 holes, Microspline
	Sprocket	Shimano SLX CS-M7100, 12-speed, 10-51 teeth
	Chain	Shimano SLX CN-M7000, 12-speed
	Inner bearing	Shimano BB-MT501B, für Hollowtec II, BSA
	Bottom bracket	Shimano GRX FC-RX610-1, Hollowtech II, 40 teeth, (170 / 170 / 172,5 / 172,5 / 175 mm)
	Gear ratio (f:r)	40 teeth : 10-51 teeth