



GXQ-400

Shimano Cues U6000 2 x 10-speed / disc

Article	Inch	Frame size	Color
102620171	28"	Gents, 48 cm	ebony matt
102620172	28"	Gents, 51 cm	ebony matt
102620173	28"	Gents, 54 cm	ebony matt
102620174	28"	Gents, 57 cm	ebony matt
102620175	28"	Gents, 60 cm	ebony matt
102620181	28"	Gents, 48 cm	cosmic silver glossy
102620182	28"	Gents, 51 cm	cosmic silver glossy
102620183	28"	Gents, 54 cm	cosmic silver glossy
102620184	28"	Gents, 57 cm	cosmic silver glossy
102620185	28"	Gents, 60 cm	cosmic silver glossy

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	25 CrMo 4, double butted, suspension-fork-ready
	Head set	Acros AZX-228, 1 1/8"-1,5", external cup
	Fork	vsf fm steel, 12 x 100 mm, Flatmount, tapered
	Shifting System	Shimano Cues RD-U6020-10, 10-speed
	Derailleur	Shimano Cues FD-U6030, 2-speed
	Brakes	Shimano Cues BR-U6030 (front 160 mm / rear 160 mm), flatmount
	Headlight	Busch & Müller Lumotec Dopp N Plus, 35 LUX
	Rear light	Trelock, LS654
	Carrier	Racktime Light-it
	Saddle	Selle Italia Model Y
	Seat post	Ritchey WCS Carbon Link Flexilogic, 27.2 mm, 350 mm
	Pedals	Marwi SP-450, flat pedal, black
	Kickstand	Atran Velo Parko
	Chainguard	---
Cockpit	Mudguard	SKS B55, plastic
	Other	max load 140 kg
	Weight	14,7 kg
	Stem	Levelnine, aluminium, 6°, (75 / 75 / 90 / 90 / 110 mm)
	Handlebars	Levelnine Gravel, aluminium, Flare 12°, (420 / 420 / 440 / 440 / 440 mm)
	Grips	Fizik Vento Solocush Tacky, black
Wheels/Tires/Drivetrain	Shift lever	Shimano Cues ST-U6030, 2-/10-speed
	Brake lever	Shimano Cues ST-U6030, 2-/10-speed
	Tires	Schwalbe G-One Comp K-Guard, 45 x 622
	Rims	Mach1 Cross-R23, 622x23C, 32 holes, tubeless-ready
	Spokes	Niro, black
	Front Hub	Shutter Precision PL-7, 12 x 100 mm, hub dynamo, Centerlock, 32 holes
	Rear Hub	Shimano FH-TC500, Centerlock, 32 holes
	Sprocket	Shimano CS-LG300-10, 10-speed, 11-39 teeth
	Chain	Shimano CN-LG500
	Inner bearing	Shimano BB-MT501B, für Hollowtec II, BSA
	Bottom bracket	Shimano Cues FC-U6030-2, Hollowtech II, 46/32 teeth, (170 / 170 / 172,5 / 172,5 / 175 mm)
	Gear ratio (f:r)	46/32 teeth : 11-39 teeth